

# radius

## PANEL

Type: a-Si TFT Active Matrix LCD  
Size: 23.1" Diagonal  
Pixel Pitch: 0.294mm(H) x 0.294mm(V)  
16.7 Million Maximum Displayable Colors

## MAXIMUM RESOLUTION

1600 x 1200 @ 75Hz

## BRIGHTNESS

250cd/m<sup>2</sup> typical

## CONTRAST RATIO

400:1 typical

## VIEWING ANGLE

85°/85°/85°/85°(T/B/L/R)

## FREQUENCY

Horizontal: 30~82KHz  
Vertical: 50~75Hz  
Maximum Pixel Rate: 162MHz

## PLUG & PLAY

DDC: 1/2B

## POWER

Universal Input Voltage 90~264 VAC, 50~60Hz  
Power Consumption: 120W max.

## OSD CONTROL

Contrast/Brightness, H/V Position, Horizontal Size, Phase, Zoom, Color Temperature, Audio, Scaling, Sharpness, ViewMeter, Input Select, Language, OSD Position, Recall

## INPUT SIGNAL

Video Input: Analog 15-pin D-Sub (R,G,B) & DVI Digital  
Sync Type: H.V. Separate,  
H.V. Composite (TTL Compatible)

## REGULATORY APPROVALS

UL, cUL, FCC Doc, VCCI, CISPR 22 B, BSMI2, CE, EPA, Energy 2000

## DIMENSIONS

Panel: 564mm(W) x 245mm(D) X 574mm(H)  
22.2"(W) x 9.6"(D) x 22.6"(H)  
Box: 688mm(W) x 686mm(D) x 368mm(H)  
27.1"(W) X 27.4"(D) X 14.5"(H)

## WEIGHT

Net: 19.5 Kg. (43.0 lbs.)  
Gross: 27.3 Kg. (60.1 lbs.)

## WARRANTY

3 Year Limited Parts and Labor  
KDS Advanced Replacement Express Service

## OTHERS

PC & Mac\* Compatible  
Tilt Angle: -5, +20°  
Swivel: 90°

# Rad-23

## 23" Analog/Digital LCD Panel



## 23" Analog/Digital LCD Flat Panel



[www.kdsusa.com](http://www.kdsusa.com)

**KDS**

©2002 KDS USA Inc. All rights reserved. Specifications, design, availability and warranty subject to change without notice.  
This document is used for reference only. KDS USA is not responsible for any errors. \*Mac adapters may be required.